


Fiber Optic Termination Box for 19-inch Rack Mounting (Fixed Enclosure) FTB-223A Series


Patch Panel Body



FTB-223A-104SC-WMP


Simplified Structure

FTB-223A- * * SC



Connection Example

FTB-223A-24SC, -48SC, -104SC



Contact us

Features

- Supports 0.25 mm / 0.9 mm single fiber and 4 fiber ribbon optical cables.
- Enabling swift construction by simply pulling the latch button on the back for ease removing the upper lid.
- Lighter than conventional products by utilizing aluminum as the main material.

Specifications

Item	Model Number	FTB-223A Series		
		FTB-223A-24SC	FTB-223A-48SC	FTB-223A-104SC
Enclosure Type		Fixed Enclosure		
Number of Connector Connections		24	48	104
Maximum number of Fusion Splices	Single Fiber(0.25 mm)	24	48	-
	Single Fiber(0.9 mm)	24	48	-
	4 Fiber Ribbon	60	80	120
Dimensions		W 482 x D 250 x H 43 (mm)	W 482 x D 250 x H 88 (mm)	W 482 x D 250 x H 88 (mm)
Applicable cable	Input	Round Cable, Ø 14 mm or less (3 cables)		
	Output	Adapter Output		
Weight		Approx. 1.8 kg	Approx. 2.5 kg	Approx. 2.7 kg
Options(Wire Guide)		Add following at the end of model number Without wire guide : -N With wire guide : -WMP		

Model Number Example

Without Wire Guide: FTB-223A-24SC-N, FTB-223A-48SC-N, FTB-223A-104SC-N

With Wire Guide: FTB-223A-24SC-WMP, FTB-223A-48SC-WMP, FTB-223A-104SC-WMP

Note: Optical fiber cords for internal wiring are not included. Contact us for the availability of pre-wiring type.



Contact us